



Notes

- ① Kalzip 65/400 aluminium standing seam top sheet.
- ② Kalzip Thermal Insulation Plus xx, 2x100mm compressed to 180mm.
- ③ E180 clip.
- ④ 99, 5x55x1, 8mm galvanised steel sub purlin S280GD+2275
- ⑤ Eaves Filler
- ⑥ 100mm Kalzip Insulation 23 2400mmx1200mm boards
- ⑦ S.F.S R45X65/BS-4, 8x70 (Four per board positioned 100mm minimum from corners. Fixed into crowns of liner
- ⑧ Aluminium Eaves Closure - Min thickness 0.9mm
- ⑨ Kalzip clear vapour control layer.
- ⑩ Kalzip trapezoidal steel liner sheet to suit Kalzip top sheet (wide rib up).
- ⑪ Cold rolled galvanised steel purlin (by others)
- ⑫ Liner Filler.
- ⑬ Internal Eaves Flashing
- ⑭ Dip angle.
- ⑮ TPO membrane-lined gutter.
- ⑯ S.F.S Intec SXCS-S19-5, 5x163 fixed through crowns of liner and into purlin
- ⑰ Galvanised steel support rail (By others)

Revision	Drawn	CHK'D	Date	Description
----------	-------	-------	------	-------------



Kalzip Ltd
Haydock Lane, Haydock, St. Helens
MERSEYSIDE, WA11 9TY

Tel: 01942 295 500
Fax: 01942 295 508

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.

Project:

Kalzip Standard Details

Client:

Kalzip Ltd

Title:

Hipped Valley Gutter

Scale:	Date:	Drawn:	Checked:
N/A	28.02.08	J.S.	
Dwg No.	KAL-0-DS-LOWU-6-001		Rev. A