



305x165x4UB
STEELWORK BY OTHERS.

15x2mm THICK
HODGSON HP500
BUTYL TAPE
SEAL.
25/40/70/40/40/25x1.6mm THICK
GALVANISED STEEL TOPHAT
SUPPORT.

200/75x0.7mm THICK
STEEL CLOSURE
FLASHING FINISHED IN
BRIGHT WHITE.
REF:G777
ZINC CLADDING,
SUPPORT SYSTEM
AND INSULATION
BY OTHERS.

ZINC INSECT
MESH BY
OTHERS.

BLACK LARGE
BEAD FOAM
FILLER BLOCK.

10/115/130/175x2.0mm
THICK ALUMINIUM
CLOSURE FLASHING
PVF2 COATED TO
RAL9006, REF:C777

10/320/638/150/44/10x2.0mm
THICK ALUMINIUM MONORIDGE
FASCIA FLASHING PVF2 COATED
TO RAL9006, REF:C777

1. All Dims in mm Unless Otherwise Stated
2. Do Not Scale From This Drawing
3. Isolate All Dissimilar Materials With Barrier Tape
4. If in Doubt, ASK

Notes



Kalzip Ltd
Haydock Lane, Haydock, St. Helens
MERSEYSIDE, WA11 9TY
Tel: 01942 717072
Fax: 01942 715713

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.

Project

Double Skin Constructions

Client:

Kalzip

Title:

Typical Kalzip Monoridge
Detail Along GL-H

Scale: 1:10 Date: 23/02/07 Drawn: KRT Checked:

Dwg No. KZ-0-DS-D-2-005 Rev: F