

Notes

- ① Kalzip 65/400 aluminium standing seam top sheet.
- ② Kalzip Thermal insulation Plus xx, 2x100mm compressed to 180mm.
- ③ E180 clip.
- ④ 99.5x55x1.8mm galvanised steel sub purlin, Grade S280GD+Z275
- ⑤ S.F.S Intec. SDK3 6.0x45.
- ⑥ 100mm Kalzip Insulation 23 2400mmx1200mm boards
- ⑦ S.F.S R45x65BS-4.8x70 (four per board positioned 100mm minimum from corners. Fixed into crowns of liner
- ⑧ Aluminium Verge Flashing - Min thickness 0.9mm
- ⑨ Kalzip clear vapour control layer.
- ⑩ Kalzip trapezoidal steel liner sheet to suit Kalzip top sheet (wide rib up).
- ⑪ Cold rolled galvanised steel purlin (by others)
- ⑫ Internal flashing.
- ⑬ Gable End Clip
- ⑭ Gable channel.
- ⑮ Tolerance gable profile.
- ⑯ S.F.S Intec SD8 liner fixings.
- ⑰ Kalzip trapezoidal liner sheet as cladding (steel / Aluminium)
- ⑱ Liner filler

Revision	Drawn	CHK'D	Date	Description
----------	-------	-------	------	-------------



Kalzip Ltd
Haydock Lane, Haydock, St. Helens
MERSEYSIDE, WA11 9TY
Tel: 01942 295 500
Fax: 01942 295 508

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.

Project:

Kalzip Standard Details

Client:

Kalzip Ltd

Title:

Verge Abutment To Cladding

Scale:	Date:	Drawn:	Checked:
N/A	16.12.08	J.S.	
Dwg No.	KAL-0-DS-LOWU-4-003	Rev.	A