

Typical Specification

- 1 Kalzip 65/400 aluminium standing seam top sheet.
- 2 Kalzip Thermal insulation Plus xx, 2x100mm compressed to 180mm.
- 3 E180 clip with M6 nut and bolt fixed point
- 4 1.6mm minimum galvanised steel top hat, 40x100x100x40mm. Grade S280GD+Z275
- 5 S.F.S Intec. SDK3 6.0x45.
- 6 100mm Kalzip Insulation 23 2400mmx1200mm boards
- 7 S.F.S R45x65/BS-4-8x70 (Four per board positioned 100mm minimum from corners. Fixed into crowns of liner
- 8 1.6mm minimum galvanised steel saddle to support top hat section. Grade S280GD+Z275.
- 9 Kalzip clear vapour control layer.
- 10 Kalzip trapezoidal steel liner sheet to suit Kalzip top sheet (wide rib up).
- 11 Cold rolled galvanised steel purlin (by others)
- 12 Internal Liner Closure Flashing.
- 13 25mm EPDM profile fillers sealed top and bottom with strip sealant.
- 14 Ridge flashing.
- 15 Ridge closure and closure filler.
- 16 'Z' Spacer profile.
- 17 1.6mm Galvanised Top hat ridge tie

Notes

- 1. All Dims in mm Unless Otherwise Stated
- 2. Do Not Scale From This Drawing
- 3. Isolate All Dissimilar Materials with Barrier Tape
- 4. If in Doubt, ASK

Revision	Drawn	CHK'D	Date	Description
----------	-------	-------	------	-------------



Kalzip Ltd
Haydock Lane, Haydock, St. Helens
MERSEYSIDE, WA11 9TY

Tel: 01942 295 500
Fax: 01942 295 508

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.

Project: Kalzip Standard Details

Client:

Kalzip Ltd

Title:

Kalzip Low U-value Liner System
Duo Pitched Ridge

Scale:	Date:	Drawn:	Checked:
1:4 @ A3	28.02.08	JS	WKA
Dwg No.	KAL-0-DS-LOWU-2-001		Rev. B

