



COVER STRIP OVER UN-SHEETED EDGE. MECHANICALLY ZIPPED INTO PLACE.  
KAL-ZIP SHEETS LAID AS NORMAL (SHOWN HERE LEFT TO RIGHT).  
SHORT SHEET LENGTH SUPPORTED ON 'ADDITIONAL' CLIP. ENSURE SUFFICIENT  
THERMAL EXPANSION ALLOWANCE.

'ADDITIONAL' CLIP MUST BE FIXED TO TRIMMED OUT STEELWORK SUPPORT.  
SHORT SHEET HAS STIFFENING RIBS CUT OUT TO SUIT TRANSITION SHEET.  
ADD ROOFLIGHT PROFILED FILLER TO TOP OF SUPPORT BAR (NOT SHOWN)

System Specification

PERFORMANCE

U-Value Triple Skin (14-20% Roof Area)	TBC	W/m <sup>2</sup> K
U-Value Double Skin (<14% Roof Area)	TBC	W/m <sup>2</sup> K
F - Factor (Triple Skin)	TBC	
F - Factor (Double Skin)	TBC	
Humidity Classes	TBC	



Kalzip Ltd  
Haydock Lane, Haydock, St. Helens  
MERSEYSIDE, WA11 9TY  
Tel: 01942 717072  
Fax: 01942 715713

This drawing is copyright and is issued on the express condition  
that it is not to be copied or disclosed by or to any unauthorised  
person or firms without prior consent in writing from Kalzip Ltd.

Title: Kalzip Site Assembled GRP RL800  
Rooflight, Foot Detail #3/6

Scale: NTS Date: 01/10/02 Drawn: JW Checked:

Dwg No. KLGRP800-A-04 Rev: A