




NOTE:  
All combustible materials are to be removed from the vicinity of the joint to ensure that there will be no fire risk due to site welding.

**SECTION 'B-B'**

NOTE:  
X = Expansion Gap



**Roof Hatch fixed to Kerb Steel using Anchor Clip**



**SECTION 'A-A'**



PLAN  
(Roof Hatch omitted for clarity)

**Notes**

1. All Dims in mm Unless Otherwise Stated
2. Do Not Scale From This Drawing
3. Isolate All Dissimilar Materials With Barrier Tape
4. If in Doubt, ASK

Revision	Drawn	CHK'D	Date	Colour Scheme and Layout
B	JPK	-	10-20-12	
<p>This drawing is copyright and is issued on the express condition that it is not to be copied or disseminated by or to any unauthorised person or firms without prior consent in writing from Kalzip.</p>				
<p>Client: <b>Kalzip Ltd</b></p>				
<p>Project: <b>Kalzip</b></p>				
<p>Title: <b>Double Skin Welded Soaker with Roof Hatch</b></p>				
Scale:	Date:	Drawn:	Checked:	
NTS	29-06-06	KRT	-	
Dwg No.	KZ-0-RH-B-34-001			Rev: <b>B</b>



A Tria Steel Enterprise

Kalzip Ltd

Haydock Lane, Haydock, St. Helens

MERSEYSIDE, WA1 1 9TY

Tel: 01942 295 500

Fax: 01942 295 508

**FOR GUIDANCE ONLY**