



ROOF PITCH $\geq 1.5^\circ$

ALUMINIUM RIDGE FLASHING.
FLASHING MAY BE FABRICATED
TO VARYING PROFILES TO SUIT
AESTHETIC REQUIREMENTS



[NOTE - FOR RIDGE FIXING DETAILS REFER TO DRG. STD-1-01]



CONTINUOUS EXTRUDED 50 x 6 mm ALUMINIUM FLAT BAR (0217), OR 22 x 6 mm ALUMINIUM FLAT BAR (0403) RIVETTED TO KALZIP SEAMS WITH Ø4.8 mm x APPROX. 15 mm LONG ALUMINIUM BLIND SEALED TYPE RIVETS (WITH STAINLESS STEEL MANDREL).

DO NOT RIVET AT ST. CLIP POSITIONS

N.B. THIS DETAIL IS APPLICABLE WHEN NO VENTILATION IS REQUIRED AT RIDGE POSITION AND WHEN 'FIXED POINT' HAS BEEN INTRODUCED AT RIDGE CLIPS

1. All Dims in mm Unless Otherwise Stated
2. Do Not Scale From This Drawing
3. Isolate All Dissimilar Materials With Barrier Tape
4. If in Doubt, ASK



A Tata Steel Enterprise

Kalzip Ltd

Haydock Lane, Haydock, St. Helens
MERSEYSIDE, WA11 9TY

Tel: 01942 717072 Fax: 01942 715713

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.

Title: Kalzip Ridge Flashing Fixing Detail

Project: Kalzip Standard Details

Client: Kalzip Ltd

Scale: 1:2	Date: 13.07.05	Drawn: KRT	Checked:
Dwg No. KZ-0-STD-K-2-002			Rev: D

ALTERNATIVE RIDGE FLASHING SUPPORT